Reply to October 19, 2005 Office Action

Art Unit 1746 Page 4 of 19

Amendments to the Claims

1. (Currently amended) A tub of a drum type washing machine,

comprising:

a tub body having a drum installed rotatably inside;

a sump having a center position and located at a bottom of the tub body to

store water or foam;

a drain outlet at a bottom of the sump located between a side of the sump

and the center position of the sump wherein the water or foam is discharged via

the drain outlet; and

a rib at [[one]] said side of the sump to prevent the water or foam from

deviating from the sump.

2-3. (Canceled).

4. (Currently amended) The tub as claimed in claim [[2]] 1, wherein

the rib is formed at an edge top of the expanded said side of the sump to prevent

water or foam from deviating from the sump [[by]] during a rotation of the drum.

5-6. (Canceled)

Reply to October 19, 2005 Office Action

Art Unit 1746 Page 5 of 19

7. (Currently Amended) The tub as claimed in claim [[5]] 1, wherein

the rib is formed at an edge top of the expanded sump to prevent the water or

foam from deviating from the sump [[by]] during a rotation of the drum.

8. (Currently Amended) A drum type washing machine, comprising:

a cabinet forming an exterior;

a drum in the cabinet to hold a laundry and a detergent therein;

a tub body having the drum installed rotatably inside;

a sump having a center position and located at a bottom of the tub body to

store water or foam;

a drain outlet at a bottom of the sump located between a side of the sump

and the center position of the sump wherein the water or foam is discharged via

the drain outlet; and

a rib at [[one]] said side of the sump to prevent the water of foam from

deviating from the sump.

9-10. (Canceled)

11. (Currently amended) The drum type washing machine as claimed in

claim [[9]] 8, wherein the rib is formed at an edge top of the expanded sump to

Application No.: 10/721,339

Reply to October 19, 2005 Office Action

Attorney Docket No. 0465-1092P Art Unit 1746

Page 6 of 19

prevent the water or foam from deviating from the sump by a rotation of the

drum.

12-13. (Canceled)

14. (Currently amended) The drum type washing machine as claimed in

claim [[12]] 8, wherein the rib is formed at an edge top of the expanded sump to

prevent the water or foam from deviating from the sump [[by]] during a rotation

of the drum.

15. (New) The drum type washing machine of claim 8, further

comprising:

a tub fixing packing located at a bottom center of the sump.

16. (New) A tub for a washing machine, comprising:

a tub body having a drum rotatably installed inside;

a sump extending along a bottom portion of the tub body to store water

and/or foam, the sump depth increasing along a rotational direction of the

drum; and

a drain outlet in the sump for discharging water or foam therethrough.

Reply to October 19, 2005 Office Action Art Unit 1746
Page 7 of 19

17. (New) The tub of claim 16, wherein the drain outlet is located in an

increased depth portion of the sump.

18. (New) The tub of claim 16, further comprising a rib provided at the

sump.

19. (New) The tub of claim 18, wherein the rib is located at an increased

depth portion of the sump.

20. (New) The tub of claim 18, wherein the rib is located at an edge of

the sump.

21. (New) The tub of claim 18, wherein the rib extends in a direction

counter to the rotational direction of the tub.

22. (New) The tub of claim 16, wherein the sump depth increases in the

rotational direction of the tub and decreases in a direction counter to the

rotational direction of the tub.

23. (New) The tub of claim 16, wherein the depth of the sump is

gradually increased in a rotational direction of the tub.

Reply to October 19, 2005 Office Action

Art Unit 1746 Page 8 of 19

24. (New) A tub for a washing machine, comprising:

a tub body having a drum rotatably installed inside;

a sump at a bottom of the tub body to store water and/or foam, wherein

the sump depth increases in a rotational direction of the tub and decreases in a

direction counter to the rotational direction of the tub.

25. (New) A washing machine, comprising:

a cabinet;

a drum in the cabinet to hold a laundry and a detergent therein;

a tub body having the drum rotatably installed inside;

a sump at the bottom of the tub body to store water and/or foam, wherein

the sump depth increases in a rotational direction of the drum; and

a drain outlet at a bottom of the sump for discharging the water and/or

foam therethrough.